

HURRICANE S5 CI SRC



DESCRIERE	NORMA EN ISO 20345:2011	REZULTAT	CERINTE
FETE: PU	5.4.2 Grosime 5.4.4 Modul de alungire pana la 100 % 5.4.5 Rezistenta la flexare:	3,32 mm 3,4 N/mm ² 280 % Fara fisuri pana la 150.000 flexari	≥ 1,00 mm 1,3 to 4,6 N/mm ² ≥ 250 % Fara fisuri pana la 150.000 flexari
BOMBEU: Otel	5.3.2.6 Rezistenta la impact 5.3.2.7 Rezistenta la compresiune	15,5 mm 18,0 mm	≥ 14 mm ≥ 14 mm
LAMELA ANTIPERFORATIE: Otel inoxidabil	6.2.1.1.3 Determinarea rezistentei la penetrare	1422 N	Min. 1100 N
TALPA: PU	5.8.3 Rezistenta la sfasiere 5.8.4 Rezistenta la abraziune 5.8.5 Rezistenta la flexare 6.4.2 Rezistenta la uleiuri 5.3.5.3 Rezistență la alunecare pe placi de otel acoperite cu glicerina (talpa joasa) (încălnat spre călcâi cu 7°) 5.3.5.2 Rezistență la alunecare pe placi spalate cu detergent (talpa joasa) (încălnat spre călcâi cu 7°)	13,4 kN/m 0,79 g/cm ³ 224 mm ³ 1,7 mm 3,1 % 0,19 0,13 0,51 0,41	≥ 8 kN/m 0,9 g/cm ³ ≤ 250 mm ³ ≤ 4,0 mm ≤ 12% ≥ 0,18 ≥ 0,13 ≥ 0,32 ≥ 0,28



GREUTATE: (KG)

37	38	39	40	41	42	43	44	45	46	47	48	49
0.763	0.810	0.857	0.904	0.951	0.998	1.045	1.092	1.139	1.186	1.233	1.280	1.327