

EVEREST_BLACK S3 CI WR SRC



DESCRIERE	NORMA EN ISO 20345:2011	REZULTAT	CERINTE
FETE: Piele Nubuck hidrofovizata	5.4.3 Rezistenta la rupere 5.4.6 Permeabilitatea vaporilor de apa Coeficient	255 N 5,1 mg/cm ² h 31,4 mg/cm ²	≥120 N ≥ 0,8 mg/cm ² h ≥ 15,0 mg/cm ²
CAPTUSEALA Membrană respirabilă lipită la cald	5.5.1 Rezistenta la rupere 5.5.2 Rezistenta la abraziune(umed)Rezistenta la abraziune(uscata) 5.5.3 Permeabilitatea vaporilor de apa Coeficient	52 N No holes No holes 5,0 mg/cm ² h 29,5 mg/cm ²	≥ 15 N 25.600 cycles 12.800 cycles ≥ 2,0 mg/cm ² ≥20,0 mg/cm ²
BOMBEU: Nemetalic, din policarbonat	5.3.2.3 Rezistenta la impact 5.3.2.4 Rezistenta la compresiune	14,5 mm 17,0 mm	≥ 14 mm ≥ 14 mm
LAMELA ANTIPERFORATIE: Nemetalica	5.7.1. Grosime 5.7.3 Absorbția apei	3,5 mm 72 mg/cm ²	≥ 2,0 mm ≥70,0 mg/cm ²
BRANT: Detasabil, respirabil, antistatic	5.7.4.2 Rezistenta la abraziune(umed) Rezistenta la abraziune (uscata)	Fara gauri	25.600 cycles 12.800 cycles
OUTSOLE: PU 2D, Antislip sole, SRC	5.8.2 Rezistenta la rupere 5.8.3 Rezistenta la abraziune 5.8.4 Rezistenta la flexare 5.8.5 Hidroliza 6.4.2 Rezistenta la uleiuri 5.11 Rezistenta la alunecare pe placi ceramice spalate cu detergent Alunecare pe talpa Alunecare pe calcai Rezistenta la alunecare pe placi de otel acoprite cu glicerina Alunecare pe talpa alunecare pe calcai	8,3 kN/m 85 mm ³ 2,00 mm 3,00 mm 1% 0,33 0,29 0,21 0,16	≥ 8 kN/m ≤ 150 mm ³ ≤ 4,0 mm ≤ 6,0 mm ≤ 12% ≥ 0,32 ≥ 0,28 ≥ 0,18 ≥ 0,13
SIZES: 35-48; MONDOPOINT: 11			