

D203 O1 FO SRC



DESCRIERE	NORMA EN ISO 20347:2012	RESULTAT CERINTE NORMA	
Fete: Microfibra	5.4.3 Rezistentă la sfasiere 5.4.6 Coeficient de Permeabilitatea la vapori de apa	102 N 1.6 mg/cm ² h 16.6 mg/cm ²	≥60 N ≥ 0,8 mg/cm ² h ≥ 15,0 mg/cm ²
Captuseala caputa : Material textil perforat, rezistentă la abraziune, antibacterian	5.5.1 Rezistentă la sfasiere 5.5.2 Rezistentă la abraziune (mediu umed) Rezistentă la abraziune (mediu uscat) 5.5.3 Permeabilitatea vaporilor de apa Coeficient de permeabilitate	30 N Fara decupaj Fara decupaj 4.4mg/cm ² h 37.9 mg/cm ² h	≥ 15 N 25.600 cicluri 12.800 cicluri ≥ 2,0 mg/cm ² ≥20,0 mg/cm ²
Captuseala stail: Tesătură respirabilă, rezistentă la abraziune, antibacterian	5.5.1 Rezistentă la sfasiere 5.5.2 Rezistentă la abraziune (mediu umed) Rezistentă la abraziune (mediu uscat) 5.5.3 Permeabilitatea vaporilor de apa Coeficient de permeabilitate	30 N Fara decupaj Fara decupaj 4.4 mg/cm ² h 37.9 mg/cm ² h	≥ 15 N 25.600 cicluri 12.800 cicluri ≥ 2,0 mg/cm ² ≥20,0 mg/cm ²

Acoperis de brant: Detasabil,anatomic, antistatic,	5.7.4.2 Rezistenta la abraziune (mediu umed) Rezistenta la abraziune (mediu uscat)	Fara perforatii Fara perforatii	25.600 cicluri 12.800 cicluri
Talpa: PU 1D, antialunecare SRC	5.8.2 Rezistenta la sfasiere 5.8.3 Rezistenta la abraziune 5.8.4 Rezistenta la flexare 5.8.5 Hidroliza 6.4.2 Rezistenta la uleiuri 5.11 Rezistenta la alunecare pe placi ceramice spalate cu detergent Alunecare pe suprafata totala a talpii Alunecare pe calcai Rezistenta la alunecare pe placi din otel acoperite cu glicerina Alunecare pe suprafata totala a talpii Alunecare pe calcai	7 kN/m 172 mm ³ 3.0 mm 4 mm 0.5% 0,43 0,35 0,22 0,16	≥ 5 kN/m ≤250mm ³ ≤ 4,0 mm ≤ 6,0 mm ≤ 12% ≥ 0,32 ≥ 0,28 ≥ 0,18 ≥ 0,13

MARIMI : 35-47

EXENA S.r.l.

Via Breda, 7/A – Zona Ind.le A 62012 – CIVITANOVA MARCHE (MC) ITALY - Telefono: +39 0733 897256 - Fax: +39 0733 897519 C.F. e P. IVA: 01336080435 – Reg.Imprese MC n.01336080435 – REA MC144207
www.exena.it – info@exena.it - pec: amministrazione@pec.exena.it

D203 O1 FO SRC



DESCRIPTION	NORM EN ISO 20347:2012	RESULT	REQUIREMENT
UPPER: pierced microfiber	5.4.3 Tear strength	102 N	≥60 N
	5.4.6 Water vapor permeability	1,6 mg/cm ² h	≥ 0,8 mg/cm ² h
	Coefficient	16,6 mg/cm ²	≥ 15,0 mg/cm ²
VAMP LINING: breathable, antibacterial, abrasion resistance textile	5.5.1 Tear strength	30 N	≥ 15 N
	5.5.2 Abrasion resistance(Wet)	No fori	25.600 cycles
	Abrasion resistance(Dry)	No fori	12.800 cycles
	5.5.3 Water vapor permeability	4,4 mg/cm ² h	≥ 2,0 mg/(cm ² h)
QUARTER LINING: breathable, antibacterial, abrasion resistance textile	Coefficient	37,9 mg/cm ²	≥20,0 mg/cm ²
	5.5.1 Tear strength	30 N	≥ 15 N
	5.5.2 Abrasion resistance(Wet)	No fori	25.600 cycles
	Abrasion resistance(Dry)	No fori	12.800 cycles
FOOTBED: Removable, cushioned, antistatic insole.	5.5.3 Water vapor permeability	4,4 mg/cm ² h	≥ 2,0 mg/(cm ² h)
	Coefficient	37,9 mg/cm ²	≥20,0 mg/cm ²
	5.7.4.2 Abrasion resistance (Wet)	No holes	25.600 cycles
OUTSOLE: PU 1D, antislip SRC	Abrasion resistance(Dry)	No holes	12.800 cycles
	5.8.2 Tear strength	7 kN/m	≥ 5 kN/m
	5.8.3 Abrasion resistance	172 mm ³	≤ 250 mm ³
	5.8.4 Flexing resistance	3 mm	≤ 4,0 mm
	5.8.5 Hydrolisis	4,0 mm	≤ 6,0 mm
	6.4.2 Oils resistance	0,5 %	≤ 12%
	5.11 Pressed ceramic tile floor on detergent resistance		
	Flat slip	0,43	≥ 0,32
	Heel slip	0,35	≥ 0,28
	Stainless steel plate on glycerin resistance		
	Flat slip	0,22	≥ 0,18
	Heel slip	0,16	≥ 0,13

SIZES : 35-47

EXENA S.r.l.

Via Breda, 7/A – Zona Ind.le A 62012 – CIVITANOVA MARCHE (MC) ITALY - Telefono: +39 0733 897256 - Fax: +39 0733 897519

C.F. e P. IVA: 01336080435 – Reg.Imprese MC n.01336080435 – REA MC144207

www.exena.it – info@exena.it - pec: amministrazione@pec.exena.it

DECLARATIE DE CONFORMITATE CE

Producatorul

EXENA SRL

Declara ca echipamentul de protectie individuala descris in continuare.

D203

Este in conformitate cu cerintele stabilite in Regulamentul 89/686/eec si este identic cu echipamentul de protectie individuala care face obiectul CERTIFICATULUI CE DE CONFORMITATE N° **0161/24146/16** emis de

CIMAC

C.so Brodolini, 19

27029 VIGEVANO (PV)

ITALY

Și este supus procedurii stabilite de directiva 89/686/CEE, articolul nr. 11, punctul A), sub controlul organismului notificat.

Civitanova Marche lì 21.03.2018

Giacomo Bara
Sales Coordinator
EXENA SRL



EC DECLARATION OF CONFORMITY

The Manufacturer

EXENA SRL

Declares that the new PPE described hereafter.

00D203

Is in the conformity with the provisions of council directive 89/686/EEC and it is identical to the PPE which is the subject of EC CERTIFICATE OF CONFORMITY n. **0161/24146/16** issued by

CIMAC

C.so Brodolini, 19

27029 VIGEVANO (PV)

ITALY

And it is submitted to the proceedings established by the directive 89/686/EEC, article n. 11, point A), under the control of the notified organism.

Civitanova Marche li 21/03/2018

Giacomo Bara
Sales Coordinator
EXENA SRL

