

D222 S2 SRC



DESCRIERE	NORMA EN ISO 20345:2011	RESULTAT CERINTE NORMA	
Fete: Microfibră, hidrofobizată	5.4.3 Rezistență la sfășiere 5.4.6 Coeficient de Permeabilitate la vapori de apă	118 N 1.3 mg/cm ² h 17.1 mg/cm ²	≥60 N ≥ 0,8 mg/cm ² h ≥ 15,0 mg/cm ²
Captuseala caputa : Material textil perforat, rezistentă la abraziune, antibacterian	5.5.1 Rezistență la sfășiere 5.5.2 Rezistență la abraziune (mediu umed) Rezistență la abraziune (mediu uscat) 5.5.3 Permeabilitatea vaporilor de apă Coeficient de permeabilitate	43 N Fără decupaj Fără decupaj 4.3mg/cm ² h 35.3 mg/cm ² h	≥ 15 N 25.600 cicluri 12.800 cicluri ≥ 2,0 mg/cm ² ≥20,0 mg/cm ²
Captuseala stăif: Țesătură respirabilă, rezistentă la abraziune, antibacteriană	5.5.1 Rezistență la sfășiere 5.5.2 Rezistență la abraziune (mediu umed) Rezistență la abraziune (mediu uscat) 5.5.3 Permeabilitatea vaporilor de apă Coeficient de permeabilitate	43 N Fără decupaj Fără decupaj 4.3 mg/cm ² h 35.3 mg/cm ² h	≥ 15 N 51.200 cicluri 25.600 cicluri ≥ 2,0 mg/cm ² ≥20,0 mg/cm ²
Bombeu de siguranță: Oțel	5.3.2.3 Rezistență la impact 5.3.2.4 Rezistență la compresie	15.5 mm 16.5 mm	≥ 14 mm ≥ 14 mm

Acoperis de brant: Detasabil,anatomic, antistatic,	5.7.4.2 Rezistenta la abraziune (mediu umed) Rezistenta la abraziune (mediu uscat)	Fara perforatii Fara perforatii	25.600 cicluri 12.800 cicluri
Talpa: PU 1D, antialunecare SRC	5.8.2 Rezistenta la sfasiere 5.8.3 Rezistenta la abraziune 5.8.4 Rezistenta la flexare 6.4.2 Rezistenta la uleiuri 5.11 Rezistenta la alunecare pe placi ceramice spalate cu detergent Alunecare pe suprafata totala a talpii Alunecare pe calcai Rezistenta la alunecare pe placi din otel acoperite cu glicerina Alunecare pe suprafata totala a talpii Alunecare pe calcai	7 kN/m 172 mm ³ 3.0 mm 4 mm 0.5% 0,43 0,32 0,22 0,16	≥ 5 kN/m ≤250mm ³ ≤ 4,0 mm ≤ 12% ≥ 0,32 ≥ 0,28 ≥ 0,18 ≥ 0,13

MARIMI : 35-47

EXENA S.r.l.

Via Breda, 7/A – Zona Ind.le A 62012 – CIVITANOVA MARCHE (MC) ITALY - Telefono: +39 0733 897256 - Fax: +39
0733 897519 C.F. e P. IVA: 01336080435 – Reg.Imprese MC n.01336080435 – REA MC144207
www.exena.it – info@exena.it - pec: amministrazione@pec.exena.it

D222 S2 SRC



DESCRIPTION	NORMA EN ISO 20345:2011	RESULT	REQUIREMENT
UPPER: Breathable water resistant microfiber	5.4.3 Tear strength 5.4.6 Water vapor permeability Coefficient	118 N 1,3 mg/cm ² h 17,1 mg/cm ²	≥60 N ≥ 0,8 mg/cm ² h ≥ 15,0 mg/cm ²
VAMP LINING: Breathable, antibacterial, abrasion resistance	5.5.1 Tear strength 5.5.2 Abrasion resistance (Wet) Abrasion resistance (Dry) 5.5.3 Water vapor permeability Coefficient	43 N No fori No fori 4,3 mg/cm ² h 35,3 mg/cm ²	≥ 15 N 25.600 cycles 12.800 cycles ≥ 2,0 mg/(cm ² h) ≥20,0 mg/cm ²
QUARTER LINING: Breathable, antibacterial, abrasion resistance	5.5.1 Tear strength 5.5.2 Abrasion resistance (Wet) Abrasion resistance (Dry) 5.5.3 Water vapor permeability Coefficient	43 N No fori No fori 4,3 mg/cm ² h 35,3 mg/cm ²	≥ 15 N 51.200 cycles 25.600 cycles ≥ 2,0 mg/(cm ² h) ≥20,0 mg/cm ²
SAFETY TOE CAP: Steel	5.3.2.3 Impact resistance 5.3.2.4 Compression resistance	15,5 mm 16,5 mm	≥ 14 mm ≥ 14 mm
FOOTBED: Removable, cushioned, antistatic insole	5.7.4.2 Abrasion resistance (Wet) Abrasion resistance (Dry)	No holes No holes	25.600 cycles 12.800 cycles
OUTSOLE PU 1D SRC, antislip	5.8.2 Tear strength 5.8.3 Abrasion resistance 5.8.4 Flexing resistance 6.4.2 Oils resistance 5.11 Pressed ceramic tile floor on detergent resistance Flat slip Heel slip Stainless steel plate on glycerin resistance Flat slip Heel slip	7 kN/m 172 mm ³ 3 mm 4,0 mm 0,5 % 0,43 0,35 0,22 0,16	≥ 5 kN/m ≤ 250 mm ³ ≤ 4,0 mm ≤ 12% ≥ 0,32 ≥ 0,28 ≥ 0,18 ≥ 0,13

MISURE : 35- 47

DECLARATIE DE CONFORMITATE CE

Prodicatorul

EXENA SRL

Declara ca echipamentul de protectie individuala descris in continuare.

D222 S2 SRC

Este in conformitate cu cerintele stabilite in Anexa II din Regulamentul 2016/425 si este identic cu echipamentul de protectie individuala care face obiectul CERTIFICATULUI CE DE CONFORMITATE N° **F-130-01641-19** emis de

CIMAC

C.so Brodolini, 19

27029 VIGEVANO (PV)

ITALY

Civitanova Marche lì 11.07.2019

Giacomo Bara
Sales Coordinator
EXENA SRL



EXENA S.r.l.

Via Breda, 7/A – Z.na Ind. A62012 – CIVITANOVA MARCHE (MC) ITALY - Telefono: +39 0733 897256 - Fax: +39 0733 897519
P. IVA: 01336080435 - Reg. Impr. Trib . MC N. 01336080435- REA MC144207

www.exena.it – info@exena.it - pec: amministrazione@pec.exena.it

EC DECLARATION OF CONFORMITY

The Manufacturer

EXENA SRL

Declares that the new PPE described hereafter.

00D222 S2 SRC

Is in conformity with the essential requirements set out in Annex II Regulation (EU) 2016/425 and
it is identical to the PPE which is the subject of EC CERTIFICATE OF CONFORMITY

N° **F-130-01641-19** issued by

CIMAC
C.so Brodolini, 19
27029 VIGEVANO (PV)
ITALY

Civitanova Marche lì 11/07/2019

Giacomo Bara
Sales Coordinator
EXENA SRL

