

exena.

GENESYS S3L FO SC SR ESD



DESCRIPTION	NORM EN ISO 20345:2022 + A1:2024	RESULT	REQUIREMENT
UPPER: Water-repellent fabric	5.4.3 Tear strength 5.4.6 Water vapor permeability Coefficient	122 N 15,7 mg/cm ² h 127,9 mg/cm ²	≥60 N ≥ 0,8 mg/cm ² h ≥ 15,0 mg/cm ²
VAMP LINING: Breathable, abrasion resistance.	5.5.2 Tear strength 5.5.3 Abrasion resistance (Wet) Abrasion resistance (Dry) 5.5.4 Water vapor permeability Coefficient	42 N No holes No holes 139,2 mg/cm ² h 1113,9 mg/cm ²	≥ 15 N 25.600 cycles 51.200 cycles ≥ 2,0 mg/cm ² ≥20,0 mg/cm ²
QUARTER LINING: Breathable, abrasion resistance mesh	5.5.2 Tear strength 5.5.3 Abrasion resistance (Wet) Abrasion resistance (Dry) 5.5.4 Water vapor permeability Coefficient	32 N No holes No holes 126,4 mg/cm ² h 1011,6 mg/cm ²	≥ 15 N 25.600 cycles 51.200 cycles ≥ 2,0 mg/cm ² ≥20,0 mg/cm ²
COUNTER LINING:	5.5.2 Tear strength 5.5.3 Abrasion resistance (Wet) Abrasion resistance (Dry) 5.5.4 Water vapor permeability Coefficient	32 N No holes No holes 15,2 mg/cm ² h 122,6 mg/cm ²	≥ 15 N 25.600 cycles 51.200 cycles ≥ 2,0 mg/(cm ² h) ≥20,0 mg/cm ²
SAFETY TOE CAP: Fiberglass 200J	5.3.2.6 Impact resistance 5.3.2.7 Compression resistance	16,0 mm 16,0 mm	≥ 14 mm ≥ 14 mm

EXENA SRL
via Breda 20
62012 Civitanova M. MC
ITALY

REA MC144207
Reg. Impr. Trib. MC 01336080435
C.F. e P. IVA 01336080435
Cap. Soc. € 25.823,00 i.v.

+39 0733 89 72 56
info@exena.com
amministrazione@pec.exena.it

exena.com



PIERCE-RESISTANCE: Class PL anti-perforation fabric	6.2.1.1.3 Resistance to perforation	PASS	Min.1100 N
FOOTBED: Removable, cushioned, antistatic insole.	5.7.4.2 Abrasion resistance (dry)	NO HOLES	25.600 cycles
	Abrasion resistance (wet)	NO HOLES	12.800 cycles
OUTSOLE: 3 density polyurethane with Etpu insert	5.8.3 Tear strength	8,4 kN/m	≥ 8 kN/m
	5.8.4 Abrasion resistance	77 mm ³	≤ 150 mm ³
	5.8.5 Flexing resistance	2,1 mm	≤ 4,0 mm
	5.8.6 Hydrolysis	2,5 mm	≤ 6,0 mm
	6.4.2 Oils resistance	1,3 %	≤ 12%
	6.2.10 Slip resistance on ceramic with glycerin (tilted towards the heel of 7°)	0,22	≥ 0,19
	(tilted towards the tip of 7°)	0,25	≥ 0,22
	5.3.5.2 Slip resistance on ceramic with cleaning agent (tilted towards the heel of 7°)	0,34	≥ 0,31
	(tilted towards the tip of 7°)	0,39	≥ 0,36
	6.2.2.2 Antistatic	dry: 51,8 MΩ wet: 5,87 MΩ	0,1 ÷ 1000 MΩ 0,1 ÷ 1000 MΩ

SIZES: 35 – 48

WEIGHT:

35	36	37	38	39	40	41	42	43	44	45	46	47	48
760	809	858	907	956	1005	1054	1103	1152	1201	1250	1299	1348	1397

Size	EAN code
35	9091001343358
36	9091001343365
37	9091001343372
38	9091001343389
39	9091001343396
40	9091001343402
41	9091001343419
42	9091001343426
43	9091001343433
44	9091001343440
45	9091001343457
46	9091001343464
47	9091001343471
48	9091001343488

CLIENTE *CUSTOMER*

Azienda *Company* EXENA S.R.L.
P. Iva *VAT no* 01336080435
Via *Street name* VIA BREDA 20
CAP *Postcode* 62012
Città (Prov.) *City* CIVITANOVA MARCHE (MC)
Paese *Country* ITALIA

Descrizione campione	Calzatura di sicurezza art. BLAZER – ESD
<i>Sample description</i>	Safety footwear art. BLAZER – ESD



Data di emissione
Date of issue

21/05/2026

Responsabile Laboratorio Tecnologico
Technological Laboratory Manager
Andrea Boggio Marzet



1. Oggetto della valutazione *Object of evaluation:*

Safety footwear art. BLAZER – ESD

2. Requisiti specifici *Specific requirements:*

- (¹) EN 61340-5-1:2024 Elettrostatica - Parte 5-1: Protezione di dispositivi elettronici dai fenomeni elettrostatici - Prescrizioni generali
Electrostatics - Part 5-1: Protection of electronic devices from electrostatic phenomena - General requirements
- (²) EN IEC 61340-4-5:2018 Elettrostatica - Parte 4-5: Metodi di prova normalizzati per applicazioni Metodi per caratterizzare la protezione elettrostatica della combinazione di pavimentazioni e di calzature indossate da un operatore
Electrostatics - Part 4-5: Standard test methods for specific applications - Methods for characterizing the electrostatic protection of footwear and flooring in combination with a person
- (³) EN IEC 61340-4-3:2018 Elettrostatica - Parte 4-3: Metodo di prova normalizzato per applicazioni specifiche - Calzature
Electrostatics - Part 4-3: Standard test methods for specific applications - Footwear

3. Lista di riscontro *Checklist:*

Requisito normativo <i>Standard requirement</i>		Prova <i>Test</i>		Rapporto di prova <i>Test report</i>	Eseguito <i>Performed</i>
5.3.3 (¹)	Messa a terra del personale <i>Personnel grounding</i>	6.3 (²)	Resistenza elettrica verso terra <i>Resistance to ground</i>	26-1092.7	☒
		6.4 (²)	Capacità di carica <i>Chargeability</i>	26-408.6	☒
		7 (³)	Resistenza elettrica <i>Electrical resistance</i>	26-408.6	☒

4. Note *Notes:* ---

TERMINI E CONDIZIONI TERMS AND CONDITIONS

Il contenuto del presente riesame (rif. 7.1 ISO/IEC 17000:2020) si riferisce unicamente al campione presentato e alle prove riportate nel rapporto di prova di cui sopra. Questo riesame non ha validità di approvazione, certificazione, supervisione, controllo, e/o sorveglianza verso questo o qualsiasi prodotto in relazione ad esso.

Qualora esista una traduzione del presente documento, la versione bilingue (italiano e inglese) sarà considerata il testo vincolante.

The content of this conformity review (ref. 7.1 ISO/IEC 17000:2020) refers only to the sample received and to the tests reported in the above-mentioned test report. This conformity review has no validity for approval, certification, supervision and/or control towards this or whatsoever product related.

Where a translation of this document exists, the bilingual version (Italian and English) shall be considered as the authoritative text.