exena.

M183E_25 S1 FO SR

DESCRIPTION	NORM EN ISO 20345:2022 + A1:2024	RESULT	REQUIREMENT
UPPER: Microfibre	5.4.3 Tear strength 5.4.6 Water vapor permeability Coefficient	93 N 1,8 mg/cm²h 16,7 mg/cm²	≥ 60 N ≥ 0,8 mg/cm²h ≥ 15,0 mg/cm²
VAMP LINING: Breathable, abrasion resistance.	5.5.2 Tear strength 5.5.3 Abrasion resistance (Wet) Abrasion resistance (Dry) 5.5.4 Water vapor permeability Coefficient	79 N No holes No holes 5,6 mg/cm2h 45,5 mg/cm2	≥ 15 N 25.600 cycles 51.200 cycles ≥ 2,0 mg/(cm²h) ≥20,0 mg/cm²
QUARTER LINING: Breathable, abrasion resistance.	5.5.2 Tear strength 5.5.3 Abrasion resistance (Wet) Abrasion resistance (Dry) 5.5.4 Water vapor permeability Coefficient	33 N No holes No holes 21,2 mg/cm2h 169,9 mg/cm 2	≥ 15 N 25.600 cycles 51.200 cycles ≥ 2,0 mg/(cm²h) ≥20,0 mg/cm²
COUNTER LINING: Breathable, abrasion resistance.	5.5.2 Tear strength 5.5.3 Abrasion resistance (Wet) Abrasion resistance (Dry) 5.5.4 Water vapor permeability Coefficient	33 N No holes No holes 21,5 mg/cm2h 173,0 mg/cm 2	≥ 15 N 25.600 cycles 51.200 cycles ≥ 2,0 mg/(cm²h) ≥20,0 mg/cm²
SAFETY TOE CAP: Steel	5.3.2.6 Impact resistance 5.3.2.7 Compression resistance	15,5 mm 20,5 mm	≥ 14 mm ≥ 14 mm

EXENA SRL
via Breda 20
62012 Civitanova M. MC
ITALY

REA MC144207
Reg. Impr. Trib. MC 01336080435
C.F. e P. IVA 01336080435
Cap. Soc. € 25.823,00 i.v.

+39 0733 89 72 56
info@exena.com
amministrazione@pec.exena.it

exena.com

exena.

FOOTBED: Removable, cushioned, antistatic insole.	5.7.4.2 Abrasion resistance (Dry) Abrasion resistance (Wet)	No holes No holes	25.600 cycles 12.800 cycles
OUTSOLE: PU Antislip sole SR	5.8.3 Tear strength 5.8.4 Abrasion resistance 5.8.5 Flexing resistance 5.8.6 Hydrolysis 6.4.2 Oils resistance 6.2.10 Slip resistance on ceramic with glycerin (tilted towards the heel of 7°) (tilted towards the tip of 7°) 5.3.5.2 Slip resistance on ceramic with cleaning agent (tilted towards the heel of 7°) (tilted towards the tip of 7°) 6.2.2.2 Antistatic	6,7 kN/m 188 mm^3 2,4 mm 3,2 mm 6 % 0,23 0,25 0,35 0,39 Dry: 112,5 MΩ Wet: 90,21 MΩ	≥ 5 kN/m ≤ 250 mm^3 ≤ 4,0 mm ≤ 6,0 mm ≤ 12% ≥ 0,19 ≥ 0,22 ≥ 0,31 ≥ 0,36 0,1 ÷ 1000 MΩ 0,1 ÷ 1000 MΩ

SIZES: 36-48

WEIGHT: (g)

36	37	38	39	40	41	42	43	44	45	46	47	48
629	685	741	797	853	909	965	1021	1077	1133	1189	1245	1301

EXENA SRL
via Breda 20
62012 Civitanova M. MC
ITALY

REA MC144207
Reg. Impr. Trib. MC 01336080435
C.F. e P. IVA 01336080435
Cap. Soc. € 25.823,00 i.v.

+39 0733 89 72 56
info@exena.com
amministrazione@pec.exena.it

exena.com