

SIBILLA GREEN S3 CI WR SRC



DESCRIERE	NORMA EN ISO 20345:2011	RESULTAT CERINTE NORMA	
Fete: Piele Nubuck+material textile impermeabil	5.4.3 Rezistentă la sfasiere 5.4.6 Coeficient de Permeabilitatea la vapori de apă	75 N 15.8 mg/cm ² h 31.4 mg/cm ²	≥60 N ≥ 0,8 mg/cm ² h ≥ 15,0 mg/cm ²
Captuseala caputa : Thinsulate+membrana respirabila lipita la cald	5.5.1 Rezistentă la sfasiere 5.5.2 Rezistentă la abraziune (mediu umed) Rezistentă la abraziune (mediu uscat) 5.5.3 Permeabilitatea vaporilor de apă Coeficient de permeabilitate	52 N Fara decupaj Fara decupaj 5.0 mg/cm ² h 29.5 mg/cm ² h	≥ 15 N 25.600 cicluri 12.800 cicluri ≥ 2,0 mg/cm ² ≥20,0 mg/cm ²
Bombeu de siguranta: Nemetalic, din policarbonat	5.3.2.3 Rezistentă la impact 5.3.2.4 Rezistentă la compresiune	14.5 mm 17 mm	≥ 14 mm ≥ 14 mm
<u>Lamela antiperforare:</u> Lamela nemetalica	5.7.1 Grosime 5.7.3 Absorbția de apă	3,5 mm 72 mg/cm ²	≥ 2 mm ≥ 70.0mg/cm ²
Acoperis de brant: Detasabil, anatomic, antistatic,	5.7.4.2 Rezistentă la abraziune (mediu umed) Rezistentă la abraziune (mediu uscat)	Fara perforatii Fara perforatii	25.600 cicluri 12.800 cicluri

Talpa: PU 2D, antialunecare SRC	5.8.2 Rezistentă la sfasiere	8.3 kN/m	≥ 8 kN/m
	5.8.3 Rezistentă la abraziune	85 mm ³	≤ 150 mm ³
	5.8.4 Rezistentă la flexare	2 mm	≤ 4,0 mm
	5.8.5 Hidroliza	3 mm	≤ 6,0 mm
	6.4.2 Rezistentă la uleiuri	1%	≤ 12%
	5.11 Rezistentă la alunecare pe placi ceramice spalate cu detergent		
	Alunecare pe suprafața totală a talpii	0,33	≥ 0,32
	Alunecare pe calcai	0,29	≥ 0,28
	Rezistentă la alunecare pe placi din otel acoperite cu glicerina		≥ 0,18
	Alunecare pe suprafața totală a talpii	0,21	
		0,16	≥ 0,13
	Alunecare pe calcai		

MARIMI : 35-48

EXENA S.r.l.

Via Breda, 7/A – Zona Ind.le A 62012 – CIVITANOVA MARCHE (MC) ITALY - Telefono: +39 0733 897256 - Fax: +39
0733 897519 C.F. e P. IVA: 01336080435 – Reg.Imprese MC n.01336080435 – REA MC144207
www.exena.it – info@exena.it - pec: amministrazione@pec.exena.it

SIBILLA GREEN S3 CI WR SRC



DESCRIPTION	NORM EN ISO 20345:2011	RESULT	REQUIREMENT
UPPER: Textile,	5.4.3 Tear strength	75 N	≥ 60 N
	5.4.6 Water vapor permeability Coefficient	15.8 mg/cm ² h 31,4 mg/cm ²	≥ 0,8 mg/cm ² h ≥ 15,0 mg/cm ²
LINING (INTERNAL SOCK): Membrane, Breathable, abrasion resistance.	5.5.1 Tear strength	52 N	≥ 15 N
	5.5.2 Abrasion resistance (Wet)	No holes	25.600 cycles
	Abrasion resistance (Dry)	No holes	12.800 cycles
	5.5.3 Water vapor permeability Coefficient	5,0 mg/cm ² h 29,5 mg/cm ²	≥ 2,0 mg/cm ² ≥ 20,0 mg/cm ²
SAFETY TOE CAP: Non-metallic polycarbonate safety toe.	5.3.2.3 Impact resistance	14,5 mm	≥ 14 mm
	5.3.2.4 Compression resistance	17,0 mm	≥ 14 mm
PIERCE-RESISTANCE: Textile pierce proof footbed,	5.7.1. Thickness	3,5 mm	≥ 2,0 mm
	5.7.3 Water absorption	72 mg/cm ²	≥ 70,0 mg/cm ²
FOOTBED: Removable, cushioned, antistatic insole.	5.7.4.2 Abrasion resistance (Wet)	No holes	25.600 cycles
	Abrasion resistance (Dry)	No holes	12.800 cycles
OUTSOLE: PU 2D, Antislip sole, SRC	5.8.2 Tear strength	8,3 kN/m	≥ 8 kN/m
	5.8.3 Abrasion resistance	85 mm ³	≤ 150 mm ³
	5.8.4 Flexing resistance	2,00 mm	≤ 4,0 mm
	5.8.5 Hydrolysis	3,00 mm	≤ 6,0 mm
	6.4.2 Oils resistance	1%	≤ 12%
	5.11 Pressed ceramic tile floor on detergent resistance		
	Flat slip	0,33	≥ 0,32
	Heel slip	0,29	≥ 0,28
	Stainless steel plate on glycerin resistance		
	Flat slip	0,21	≥ 0,18
	Heel slip	0,16	≥ 0,13

SIZES: 35-48;
MONDOPOINT: 11

Traducere din limba engleza - in conformitate cu documentul

EXENA
DECLARATIE DE CONFORMITATE UE
M22 -Vers. 00

Conform regulamentului (UE) 2016/425 – Anexa IX, **Exena srl** DECLARA
ca echipamentul individual de protectie si lotul respectiv de productie
descrie mai jos:

Articol: **SIBILLA GREEN**

Lot: 70450



Este in conformitate cu standardul: EN ISO 20345:2011

Clasa: II

Categoria de marcaj: S3 CI WR SRC

Nr. certificat: F-130-04682-21

Data: **30.07.2021**

EMIS DE: CIMAC – 0465

Civitanova Marche,

Aplicata parafa firmei EXENA S.R.L.

Sediul in Via Breda, 7/A

Civitanova Marche (MC), ITALIA ,

Sfârșitul traducerii



DECLARATION OF CONFORMITY UE

M22 - Ver.00

As per Regulation (UE) 2016/425 - Annex IX, Exena Srl declares that the ppe and the relative production batch below described:

item

SIBILLA GREEN

batch:

70450



conforms to the standard:

EN ISO 20345:2011

class:

II

marking category:

S3 CI WR SRC

certificate numb.:

F-130-04682-21

date:

30/07/2021

issued by:

CIMAC - 0465

Civitanova Marche

EXENA S.r.l.
Via Breda, 7 - Z.na Ind. A 62012 - CIVITANOVA MARCHE (MC) ITALY
Tel. 0733 897256 fax 0733 897519
P. IVA: 01336080435 - Reg. Impr. Trib. MC N. 21676/1998 - CCIAA MC 22988
www.exena.it - info@exena.it - pec: amministrazione@pec.exena.it

EXENA S.r.l.

Via Breda, 7 - Z.na Ind. A 62012 - CIVITANOVA MARCHE (MC) ITALY - Telefono: +39 0733 897256 - Fax: +39 0733 897519

P. IVA: 01336080435 - Reg. Impr. Trib. MC N. 21676/1998 - CCIAA MC 22988

www.exena.it - info@exena.it - pec: amministrazione@pec.exena.it