PHOENIX S3 CI SRC





DESCRIERE	NORMA EN ISO 20345:2011	REZULTAT	CERINTE NORMA
Fete: Piele naturala, cu tratament rezistent la apa, insertii reflectorizante	5.4.3 Rezistenta la sfasiere 5.4.6 Coeficient de Permeabilitatea la vapori de apa	189 N 1.2 mg/cm^{2}h 18.4 mg/cm^2	≥120 N ≥ 0,8 mg/cm^{2}h ≥ 15,0 mg/cm^2
Captuseala caputa : cu aerisire si rezistenta la abraziune	5.5.1 Rezistenta la sfasiere 5.5.2 Rezistenta la abraziune (mediu umed) Rezistenta la abraziune (mediu uscat) 5.5.3 Coeficient de Permeabilitatea la vapori de apa	25 N Fara decupaj Fara decupaj 7,7 mg/cm^2 62,0 mg/cm^2	≥ 15 N 25.600 cicluri 12.800 cicluri ≥ 2,0 mg/cm^2 ≥ 20,0 mg/cm2
Captuseala staif: cu aerisire si rezistenta la abraziune	5.5.1 Rezistenta la sfasiere 5.5.2Rezistenta la abraziune (mediu umed) Rezistenta la abraziune (mediu uscat) 5.5.3 Coeficient de Permeabilitatea la vapori de apa	25 N Fara decupaj Fara decupaj 7,7 mg/cm^2 62 mg/cm^2	≥ 15 N 25.600 cicluri 12.800 cicluri ≥ 2,0 mg/cm^2 ≥ 20,0 mg/cm2
Bombeu de siguranta: Material compozit nemetalic	5.3.2.3 Rezistenta la impact 5.3.2.4 Rezistenta la compresiune	14,0 mm 14,0 mm	≥ 14 mm ≥ 14 mm
<u>Lamela antiperforare</u>: Lamelă antiperforaţie	5.7.1 Grosime 5.7.3 Absorbtia de apa	3,5 mm 72 mg/cm^2	≥ 2,0 mm ≥70,0 mg/cm^2

nemetalică, perforaţie zero			
Acoperis de brant: Talpa interioara detasabila, captusita, antistatica	5.7.4.2 Rezistenta la abraziune (mediu umed) Rezistenta la abraziune (mediu uscat)	Fara perforatii Fara perforatii	25.600 cicluri 12.800 cicluri
Talpa: PU 2D, talpa aderenta, SRC	5.8.2 Rezistenta la sfasiere 5.8.3 Rezistenta la abraziune 5.8.4 Rezistenta la flexare 5.8.5.Hidroliză 6.4.2 Rezistenta la uleiuri 5.11 Rezistenta la alunecare pe placi ceramice spalate cu detergent Alunecare pe suprafata totala a talpii Alunecare pe calcai Rezistenta la alunecare pe placi din otel acoperite cu glicerina Alunecare pe suprafata totala a talpii Alunecare pe calcai	10.4 kN/m 50 mm^3 1.5 mm 2.5 mm 1.0% 0,32 0,28 0,18 0,14	≥ 8 kN/m ≤ 150mm^3 ≤ 4,0 mm ≤ 6,0 mm ≤ 12% ≥ 0,32 ≥ 0,28 ≥ 0,18 ≥ 0,13

MARIMI : 35-48 MONDOPOINT 11

EXENA S.r.l.
Via Breda, 7/A – Zona Ind.le A 62012 – CIVITANOVA MARCHE (MC) ITALY - Telefono: +39 0733 897256 - Fax: +39 0733 897519 C.F. e P. IVA: 01336080435 – Reg.Imprese MC n.01336080435 – REA MC144207 www.exena.it – info@exena.it - pec: amministrazione@pec.exena.it

---

PHOENIX S3 CI SRC





DESCRIPTION	NORM EN ISO 20345:2011	RESULT	REQUIREMENT
UPPER: Genuine leather, water repellent treatment, reflex inserts	5.4.3 Tear strength 5.4.6 Water vapour permeability Coefficent	189 N 1,2 mg/cm²h 18,4 mg/cm²	≥120 N ≥ 0,8 mg/cm²h ≥ 15,0 mg/cm²
VAMP LINING: Breathable, abrasion resistance.	5.5.1 Tear strength 5.5.2 Abrasion resistance(Wet) Abrasion resistance(Dry) 5.5.3 Water vapor permeability Coefficient	25 N No holes No holes 7,7mg/cm²h 62,0 mg/cm²	≥ 15 N 25.600 cycles 12.800 cycles ≥ 2,0 mg/cm² ≥20,0 mg/cm²
QUARTER LINING: Breathable, abrasion resistance.	5.5.1 Tear strength 5.5.2 Abrasion resistance(Wet) Abrasion resistance(Dry) 5.5.3 Water vapor permeability Coefficient	25 N No holes No holes 7,7 mg/cm²h 62,0 mg/cm²	≥ 15 N 51.200 cycles 25.600 cycles ≥ 2,0 mg/cm² ≥20,0 mg/cm²
SAFETY TOE CAP: Non-metallic polycarbonate safety toe.	5.3.2.3 Impact resistance 5.3.2.4 Compression resistance	14,0 mm 14,0 mm	≥ 14 mm ≥ 14 mm
PIERCE-RESISTANCE: Textile pierce proof footbed,	5.7.1. Thickness 5.7.3 Water absorption	3,5 mm 72 mg/cm²	≥ 2,0 mm ≥70,0 mg/cm²
FOOTBED: Removable, cushioned, antistatic insole.	5.7.4.2 Abrasion resistance(Wet) Abrasion resistance(Dry)	No holes No holes	25.600 cycles 12.800 cycles
OUTSOLE: PU 2D, Antislip sole, SRC	5.8.2 Tear strength 5.8.3 Abrasion resistance 5.8.4 Flexing resistance 5.8.5 Hydrolysis 6.4.2 Oils resistance 5.11 Pressed ceramic tile floor on detergent resistance Flat slip Heel slip Stainless steel plate on glycerin resistance Flat slip Heel slip	10,4 kN/m 50 mm³ 1,5 mm 2,5 mm 1% 0,32 0,28 0,18 0,14	≥ 8 kN/m ≤ 150 mm³ ≤ 4,0 mm ≤ 6,0 mm ≤ 12% ≥ 0,32 ≥ 0,28 ≥ 0,18 ≥ 0,13

SIZES : 35-48

EXENA S.r.l.
Via Breda, 7/A – Zona Ind.le A 62012 – CIVITANOVA MARCHE (MC) ITALY - Telefono: +39 0733 897256 - Fax: +39 0733 897519
C.F. e P. IVA: 01336080435 – Reg.Imprese MC n.01336080435 – REA MC144207
www.exena.it – info@exena.it - pec: amministrazione@pec.exena.it

---

Traducere din limba engleza - in conformitate cu documentul

EXENA

DECLARATIE DE CONFORMITATE UE

M22 –Vers. 00

Conform regulamentului (UE) 2016/425 – Anexa IX, **Exena srl** DECLARA ca echipamentul individual de protectie si lotul respectiv de productie descris mai jos:

Articol: **PHOENIX**

Lot: 68521



Este in conformitate cu standardul: EN ISO 20345:2011

Clasa: II

Categoria de marcaj: S3 CI SRC

Nr. certifcat: F-130-04529-21

Data: **03.06.2021**

EMIS DE: CIMAC – 0465
Civitanova Marche

Aplicata parafa firmei EXENA S.R.L.

Sediul in Via Breda, 7/A

Civitanova Marche (MC), ITALIA ,

Semnatura ilizibila

Sfârşitul traducerii

DECLARATION OF CONFORMITY UE

M22 - Ver.00

As per Regulation (UE) 2016/425 - Annex IX, Exena Srl declares that the ppe and the relative production batch below descripted:

item	**PHOENIX**
batch:	**68521**



conforms to the standard:	**EN ISO 20345:2011**
class:	**II**
marking category:	**S3 CI SRC**
certificate numb.:	**F-130-04529-21**
date:	**03/06/2021**
issued by:	**CIMAC - 0465**

Civitanova Marche

EXENA S.r.l.
Via Breda, Z.I.A. - Zona Ind.le A
Tel. 0733 897256 Fax 0733 897519
62012 CIVITANOVA MARCHE - MC
P. IVA 01336080435

CEO

EXENA S.r.l.

Via Breda, 7 – Z.na Ind. A 62012 – CIVITANOVA MARCHE (MC) ITALY - Telefono: +39 0733 897256 - Fax: +39 0733 897519

P. IVA: 01336080435 - Reg. Impr. Trib . MC N. 21676/1998 - CCIAA MC 22988

www.exena.it – info@exena.it - pec: amministrazione@pec.exena.it