

XR89 BOULEVARD S3 SRC



DESCRIERE	NORMA EN ISO 20345:2011	RESULTAT CERINTE NORMA	
Fete: Microfibră și material textil respirabil	5.4.3 Rezistența la sfasiere 5.4.6 Coeficient de Permeabilitatea la vapori de apă 6.3 Absorbție de apă Penetrație	76 N 3.4 mg/cm ² h 29 mg/cm ² 23% 0.0 g	≥60 N ≥ 0,8 mg/cm ² h ≥ 15,0 mg/cm ² ≤ 30% ≤ 0,2 g
Captuseala caputa : Material textil perforat, rezistent la abraziune, asigură aerisirea piciorului	5.5.1 Rezistența la sfasiere 5.5.2 Rezistența la abraziune (mediu umed) Rezistența la abraziune (mediu uscat)	26 N Fara decupaj Fara decupaj	≥ 15 N 25.600 cicluri 12.800 cicluri
Captuseala staif: cu aerisire și rezistența la abraziune	5.5.1 Rezistența la sfasiere 5.5.2 Rezistența la abraziune (mediu umed) Rezistența la abraziune (mediu uscat)	25 N Fara decupaj Fara decupaj	≥ 15 N 51.200 cicluri 25.600 cicluri
Bombeu de siguranta: Aluminiu, rezistent la compresiune 200 j Lamela antiperforare: Lamela nemetalica, perforatie zero	5.3.2.3 Rezistența la impact 5.3.2.4 Rezistența la compresiune	14 mm 14 mm	≥ 14 mm ≥ 14 mm
	5.7.1 Grosime 5.7.3 Absorbția de apă 5.10 Antistatic (uscat)	3,6 mm 96 mg/cm ² 5.81x10 ⁸ Ω	≥ 2 mm ≥ 70.0mg/cm ² ≥100kkΩ and

	Antistatic (umed)	2.36x108 Ω	≤1000 kΩ
Acoperis de brant: X-CONTROL talpa interioara detasabila, captusita, antistatica	5.7.4.2 Rezistenta la abraziune (mediu umed) Rezistenta la abraziune (mediu uscat)	Fara perforatii Fara perforatii	25.600 cicluri 12.800 cicluri
Talpa: PU densiate mare, SRC	5.8.2 Rezistenta la sfasiere 5.8.3 Rezistenta la abraziune 5.8.4 Rezistenta la flexare 6.4.2 Rezistenta la uleiuri 5.11 Rezistenta la alunecare pe placi ceramice spalate cu detergent Alunecare pe suprafata totala a talpii Alunecare pe calcai Rezistenta la alunecare pe placi din otel acoperite cu glicerina Alunecare pe suprafata totala a talpii Alunecare pe calcai	7.4 kN/m 178 mm ³ 2 mm 4% 0,47 0,45 0,22 0,18	≥ 8 kN/m ≤250mm ³ ≤ 4,0 mm ≤ 12% ≥ 0,32 ≥ 0,28 ≥ 0,18 ≥ 0,13

MARIMI : 38-48

EXENA S.r.l.

Via Breda, 7/A – Zona Ind.le A 62012 – CIVITANOVA MARCHE (MC) ITALY - Telefono: +39 0733 897256 - Fax: +39 0733 897519 C.F. e P. IVA: 01336080435 – Reg.Imprese MC n.01336080435 – REA MC144207
www.exena.it – info@exena.it - pec: amministrazione@pec.exena.it

XR89 BOULEVARD S3 SRC



DESCRIPTION	NORM EN ISO 20345:2011	RESULT	REQUIREMENT
UPPER: Water resistant microfiber	5.4.3 Tear strength 5.4.6 Water vapor permeability Coefficient 6.3 Water absorption Water penetration	76 N 3,4 mg/cm ² h 29 mg/cm ² 23% 0,0g	≥60 N ≥ 0,8 mg/cm ² h ≥ 15,0 mg/cm ² ≤ 30% ≤ 0,2 g
VAMP LINING: Breathable, abrasion resistance.	5.5.1 Tear strength 5.5.2 Abrasion resistance(Wet) Abrasion resistance(Dry)	26 N No fori No fori	≥ 15 N 25.600 cycles 12.800 cycles
QUARTER LINING: Breathable, abrasion resistance.	5.5.1 Tear strength 5.5.2 Abrasion resistance(Wet) Abrasion resistance(Dry)	25 N No fori No fori	≥ 15 N 51.200 cycles 25.600 cycles
SAFETY TOE CAP: Aluminium 200J	5.3.2.3 Impact resistance 5.3.2.4 Compression resistance	14,0 mm 14,0 mm	≥ 14 mm ≥ 14 mm
PIERCE-RESISTANCE: Textile pierce proof footbed	5.7.1. Thickness 5.7.3 Water absorption 5.10 Antistatic (dry) Antistatic (wet)	3,6 mm 96 mg/cm ² 5,81 x10 ⁸ Ω 2,36 x10 ⁸ Ω	≥ 2,0 mm ≥70,0 mg/cm ² ≥ 100 kΩ and ≤ 1000 kΩ
FOOTBED: X-CONTROL Removable, cushioned, antistatic insole.	5.7.4.2 Abrasion resistance(Wet) Abrasion resistance(Dry)	No holes No holes	25.600 cycles 12.800 cycles
OUTSOLE: High density PU, SRC	5.8.2 Tear strength 5.8.3 Abrasion resistance 5.8.4 Flexing resistance 6.4.2 Oils resistance 5.11 Pressed ceramic tile floor on detergent resistance Flat slip Heel slip Stainless steel plate on glycerin resistance Flat slip Heel slip	7,4 kN/m 178 mm ³ 2 mm 4 % 0,47 0,45 0,22 0,18	≥ 8 kN/m ≤ 250 mm ³ ≤ 4,0 mm ≤ 12% ≥ 0,32 ≥ 0,28 ≥ 0,18 ≥ 0,13

MISURE : 38-48

EXENA S.r.l.

Via Breda, 7/A – Zona Ind.le A 62012 – CIVITANOVA MARCHE (MC) ITALY - Telefono: +39 0733 897256 - Fax: +39 0733 897519

C.F. e P. IVA: 01336080435 – Reg.Imprese MC n.01336080435 – REA MC144207

www.exena.it – info@exena.it – pec: amministrazione@pec.exena.it

DECLARATIE DE CONFORMITATE CE

Prodicatorul

EXENA SRL

Declara ca echipamentul de protectie individuala descris in continuare.

XR 89 BOULEVARD S3 SRC

Este in conformitate cu cerintele stabilite in anexa II din Regulamentul (UE) 2016/425 si este identic cu echipamentul de protectie individuala care face obiectul CERTIFICATULUI CE DE CONFORMITATE N° **F-130-02595-19** emis de

CIMAC

C.so Brodolini, 19

27029 VIGEVANO (PV)

ITALY

Civitanova Marche lì 22/07/2019

Giacomo Bara
Sales Coordinator
EXENA SRL



EXENA S.r.l.

Via Breda, 7/A – Z.na Ind. A62012 – CIVITANOVA MARCHE (MC) ITALY - Telefono: +39 0733 897256 - Fax: +39 0733 897519
P. IVA: 01336080435 - Reg. Impr. Trib . MC N. 01336080435- REA MC144207

www.exena.it – info@exena.it - pec: amministrazione@pec.exena.it

EC DECLARATION OF CONFORMITY

The Manufacturer

EXENA SRL

Declares that the new PPE described hereafter.

XR 89 BOULEVARD S3 SRC

Is in conformity with the essential requirements set out in Annex II Regulation (EU) 2016/425 and it is identical to the PPE which is the subject of EC CERTIFICATE OF CONFORMITY

N° **F-130-02595-19** issued by

CIMAC

C.so Brodolini, 19

27029 VIGEVANO (PV)

ITALY

Civitanova Marche lì 22/07/2019

Giacomo Bara
Sales Coordinator
EXENA SRL

