

MB ASUS PRIME B760M-K DDR4 LGA1700



Pret: 504⁵⁹ RON (fara TVA)

Disponibilitate: Comanda speciala

Descriere

Placa de baza ASUS PRIME B760M-K DDR4 LGA1700 Model PRIME B760M-K D4 CPU Intel® Socket LGA1700 for 13th Gen Intel® Core™ Processors & 12th Gen Intel® Core™, Pentium® Gold and Celeron® Processors* Supports Intel® Turbo Boost Technology 2.0 and Intel® Turbo Boost Max Technology 3.0** * Refer to www.asus.com for CPU support list. ** Intel® Turbo Boost Max Technology 3.0 support depends on the CPU types. Chipset Intel® B760 Chipset Memory 2 x DIMM, Max. 64GB, DDR4 5333(OC)/5066(OC)/5000(OC)/4800(OC)/4600(OC)/4400(OC)/4266(OC)/4000(OC)/3733(OC)/3600(OC)/3466(OC)/3400(OC)/3333(OC)/3200/3000/2933/2800/2666/2400/2133 Non-ECC, Un-buffered Memory* Dual Channel Memory Architecture Supports Intel® Extreme Memory Profile (XMP) * Supported memory types, data rate (speed), and number of DRAM modules vary depending on the CPU and memory configuration, for more information please refer to CPU/Memory Support list under the Support tab of product information site or visit <https://www.asus.com/support/>. Graphics 1 x VGA port 1 x HDMI® port** * Graphics specifications may vary between CPU types. Please refer to www.intel.com for any updates. ** Supports 4K@60Hz as specified in HDMI® 2.1. Expansion Slots Intel® 13th & 12th Gen Processors 1 x PCIe 4.0 x16 slot Intel® B760 Chipset 2 x PCIe 4.0 x1 slots Note: To ensure compatibility of the device installed, please refer to <https://www.asus.com/support/> for the list of supported peripherals. Storage Total supports 2 x M.2 slots and 4 x SATA 6Gb/s ports* Intel® 13th & 12th Gen Processors M.2_1 slot (Key M), type 2242/2260/2280 (supports PCIe 4.0 x4 mode) Intel® B760 Chipset M.2_2 slot (Key M), type 2242/2260/2280 (supports PCIe 4.0 x4 mode) 4 x SATA 6Gb/s ports * Intel® Rapid Storage Technology supports SATA RAID 0/1/5/10. Ethernet 1 x Realtek 2.5Gb Ethernet